



### Model Number


**V1-G-0,5M-PUR-ABG-Y222723**

Female cordset, M12, 4-pin, shielded, PUR cable

### Features

- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Shield attached to coupling nut
- Gold plated contacts
- Degree of protection IP67 / IP68 / IP69K
- Halogen-free

### Dimensions



### Technical data

#### General specifications

Number of pins 4 + shield

#### Electrical specifications

Operating voltage  $U_B$  max. 250 V AC/DC  
 Operating current  $I_B$  max. 4 A  
 Volume resistance  $< 5 \text{ m}\Omega$

#### Ambient conditions

Ambient temperature Body: -40 ... 90 °C (-40 ... 194 °F)  
 cable, flexing: -25 ... 80 °C (-13 ... 176 °F)  
 cable, fixed: -25 ... 80 °C (-13 ... 176 °F)

Pollution Degree 3

#### Mechanical specifications

Contact elements spring-loaded contact socket

Pin diameter 1 mm

Degree of protection IP67

#### Material

Contacts CuSn / Au

Contact surface Au

Body TPU, black

Cable PUR

Slotted nut Diecast zinc

Core insulation PP

Cable fine-strand, flexible

Sheath diameter  $\varnothing 4.8 \text{ mm}$

Bending radius  $> 10 \times$  cable diameter, moving  
 $5 \times$  cable diameter, single bend

Color grey

Cores  $4 \times 0.34 \text{ mm}^2$

Conductor construction  $19 \times 0.15 \text{ mm } \varnothing$

Shield grid covering 85 %

Length L 0.5 m

#### Flammability

Contact material HB

Housing V-2

Note With connector sleeves

#### Compliance with standards and directives

##### Standard conformity

Degree of protection EN 60529:2000

Standards IEC 61076-2-101:2008

Flammability Grip: UL 94

### Electrical connection

