



Model Number


V31-WR-2M-PUR

Female cordset, snap locking, 4-pin, PUR cable

Features

- Snap locking
- Halogen-free
- Resistant to microbes and hydrolysis

Dimensions



Technical data

General specifications

Number of pins	4
Connection 1	socket
Construction type 1	right angle
Connection 2	cable end

Electrical specifications

Operating voltage	U _B	max. 30 V AC/DC
Operating current		max. 4 A
Volume resistance		< 5 mΩ


Ambient conditions

Ambient temperature	-25 ... 90 °C (-13 ... 194 °F) cable, fixed: -40 ... 80 °C (-40 ... 176 °F) cable, flexing: -5 ... 80 °C (23 ... 176 °F)
Pollution Degree	3

Mechanical specifications

Degree of protection	IP65/IP67
Material	
Contacts	CuSn
Contact surface	Ni/Au
Body	TPU, black
Cable	PUR
Seal	NBR
Core insulation	PP
Cable	extra-fine wire, flexible
Bending radius	> 10 x cable diameter, moving
Color	black
Cores	4 x 0.25 mm ²
Conductor construction	32 x 0.1 mm Ø
Length	L 2 m

Electrical connection



Release date: 2014-03-25 14:59 Date of issue: 2014-03-25 226954_eng.xml