


Dimensions



Model Number

VMC-2+P/V2

Valve connector, Form C, Varistor, non pre-wired

Features

- Valve connector as per EN 175301-803
- · Varistor as a protective circuit
- Built-in LED, as operating and function indicator

Technical data

Genera	specifications	

 Number of pins
 2 + PE

 Connection 1
 Valve connector DIN

 Construction type 1
 right angle

Indicators/operating means

LED yellow Functional display

Electrical specifications

 $\begin{array}{ccc} \text{Operating voltage} & \text{U}_{\text{B}} & \text{24 V AC/DC} \\ \text{Operating current} & \text{max. 10 A} \\ \text{Volume resistance} & & <4 \, \text{m} \omega \\ \end{array}$

Ambient conditions

Ambient temperature $-25 \dots 90 \,^{\circ}\text{C} \, (-13 \dots 194 \,^{\circ}\text{F})$ Storage temperature $-40 \dots 125 \,^{\circ}\text{C} \, (-40 \dots 257 \,^{\circ}\text{F})$

Mechanical specifications

Degree of protection IP67

Connection Valve connector Form C screw terminal for max. 1.5 mm²; 16 AWG

Material

Contact surface Ag

Body PA, transparent Seal NBR

Cable

Sheath diameter 3 ... 5.5 mm

Electrical connection

