



Model Number


V15S-G-BK10M-PUR-U/ABG

Single-ended cordset, male, M12, 5-pin, PUR cable, shielded

Features

- UL Recognized Component
- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Flame resistant cable
- Halogen-free
- Appropriate for conveyor chains

Dimensions



Technical data

General specifications

Number of pins	5 + shield
Connection 1	Male connector
Construction type 1	straight
Threading 1	M12
Connection 2	cable end

Electrical specifications

Operating voltage	U_B	max. 60 V DC
Operating current		max. 4 A
Volume resistance		< 5 m Ω

Ambient conditions

Ambient temperature	Body: -25 ... 90 °C (-13 ... 194 °F) cable, flexing: -25 ... 80 °C (-13 ... 176 °F) cable, fixed: -40 ... 80 °C (-40 ... 176 °F)
Pollution Degree	3

Mechanical specifications

Protection degree	IP65 / IP67 / IP69K
Material	
Contacts	CuSn
Contact surface	Ni/Au
Body	TPU
Cable	PUR
Sleeve connector	Zinc die-casting, nickel-plated
Seal	NBR
Core insulation	PP
Cable	extra-fine wire, flexible
Sheath diameter	\varnothing 5.9 mm
Bending radius	> 10 x cable diameter, appropriate for conveyor chains > 5 x cable diameter, fixed
Color	black
Cores	5 x 0.34 mm ² ; 22 AWG
Conductor construction	42 x 0.1 mm \varnothing
Shield	grid covering 85 %
Length	L 10 m
Flammability	
Cable	FT2

Compliance with standards and directives

Standard conformity	
Protection degree	EN 60529:2000
Standards	IEC 61076-2-101:2008

Approvals and certificates

UL approval	UL Recognized General purpose
-------------	-------------------------------

Electrical connection

