

Model Number


V15B-G-0,3M-PUR-IB-V15B-G

INTERBUS bus cable, M12 to M12, PUR cable

Features

- B-coding for INTERBUS
- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Shield attached to coupling nut
- Halogen-free

Dimensions



Technical data

General specifications

Number of pins	5 + shield
Connection 1	female connector
Construction type 1	straight
Threading 1	M12
Connection 2	Male connector
Construction type 2	straight
Threading 2	M12

Electrical specifications

Operating voltage	U_B	max. 60 V
Operating current		max. 4 A
Volume resistance		< 5 m Ω

Ambient conditions

Ambient temperature	Body: -25 ... 90 °C (-13 ... 194 °F) cable, fixed: -40 ... 80 °C (-40 ... 176 °F) cable, flexing: -30 ... 70 °C (-22 ... 158 °F)
Pollution Degree	3


Mechanical specifications

Protection degree	IP65 / IP67/ IP69K	
Connection	5-pin M12 connector, B-coded	
Material		
Contacts	CuSn	
Contact surface	Ni/Au	
Body	TPU, black	
Cable	PUR	
Slotted nut	Zinc die-casting, nickel-plated	
Sleeve connector	Zinc die-casting, nickel-plated	
Seal	NBR	
Core insulation	PE	
Cable	3 pairs with 2 strands for each core	
Sheath diameter	Ø 8 mm	
Bending radius	≥ 60 mm, fixed ≥ 120 mm, agitated	
Color	green	
Cores	3 x 2 x 0.25 mm ² / 24 AWG	
Conductor construction	32 x 0.1 mm Ø	
Shield	grid tin-plated copper wires, 80 % covering	
Length	L	0.3 m

Compliance with standards and directives

Standard conformity	
Protection degree	EN 60529:2000
Standards	IEC 61076-2-101:2008

Electrical connection



Release date: 2013-04-10 10:34 Date of issue: 2013-04-12 254575_eng.xml

Subject to modifications without notice

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776-4411
fa-info@pepperl-fuchs.com

Copyright Pepperl+Fuchs
Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com



Flammability

IEC 60332-1-2:2004