


## **Features**

- Power 18 W
- Installation in Zone 1, Zone 2, Zone 21 and Zone 22
- · Ex de certified
- Multi voltage electronic ballast
- AC model
- Borosilicate glass overtube resistant to process chemicals
- Sturdy metallic housing

## Dimensions (mm)



Te	ch	nic	al	da	ıta

Electrical specifications			
Operating voltage	207 254 V 50/60 Hz		
Operating current	0.12 A		
Terminal capacity	2.5 mm <sup>2</sup>		
Control gear	high frequency electronic ballast complying with all European standards relating to safety, operation and EMC (Immunity)		
Power factor	0.98		
Fitting type	Ceiling light fitting		
Lamps	T8 bi-pin fluorescent tube , not included with delivery		
Number of lamps	1		
Length	600 mm ( 2 ft )		
Power	18 W		
EMC in accordance with	EN55015:2000		
Emergency operation	maintained or non-maintained		
Operation time	3 h		
Recharge time	24 h from fully discharged		
Ballast lumen factor	12 %		
Battery protection	Protection against deep discharge and reverse battery polarity		
Conformity			
Protection degree	EN 60529		
Ambient conditions			
Ambient temperature	-20 40 °C (-4 104 °F) / T6 / T85°C -20 50 °C (-4 122 °F) / T5 / T100°C		
Mechanical specifications			
Cover fixing	M8 stainless steel socket cap head screws		
Protection degree	IP67 according to EN 60529		

Cable entry

Number of cable entries

1 x M20 at position E fitted with Ex d sealing plug

metric threaded

Material			
Cast parts	Light metal alloy		
Lamp cover	Borosilicate glass		
Reflector	0.9 mm galvanised mild steel		
Finish	cast parts: epoxy powder coated, RAL7032 reflector: epoxy powder coated, white		
Seal	nitrile O-ring		
Mass	approx. 6.5 kg		
Dimensions			
Α	915 mm		
В	592 mm		
С	911 mm		
D	652 mm		
Mounting	2 x stainless steel removable mounting brackets		
Grounding	Internal connection		
Data for application in connection with Exareas			
EC-Type Examination Certificate	SIRA 00 ATEX 1107X		
Group, category, type of protection, temperature class			
International approvals			
IECEx approval	IECEx SIR 10.0077X		
GOST-R approval	GOST-R B01007		
General information			
Supplementary information	EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see www.pepperlfuchs.com.		