

Features

- Installation in Zone 1, Zone 2, Zone 21 and Zone 22

Dimensions (mm)**Technical data****Electrical specifications**

Operating voltage	230 V
Control gear	high frequency electronic ballast
Fitting type	Fluorescent hand lamp
Lamps	Osram / Radium 4 pin PLL 2G11
Number of lamps	1
Power	55 W
Tube O/D	56 mm
Initial lumens	4800 lm

Mechanical specifications

Cover fixing	M8 stainless steel socket cap head screws
Protection degree	IP66 / IP67
Cable entry	Ex d cable gland screwed into an M20 entry
Material	
Endcaps	aluminum
Lamp cover	Polycarbonate
Mass	approx. 1.5 kg
Dimensions	
A	795 mm
Mounting	2 x moulded suspension hooks

Ambient conditions

Ambient temperature	-20 ... 40 °C (-4 ... 104 °F)
---------------------	-------------------------------

Data for application in connection with Ex-areas

EC-Type Examination Certificate	BAS 00 ATEX 2075X
Group, category, type of protection, temperature class	⊕ II 2 GD Ex d IIB T5 Ex tD T100° A21 IP66/67

Conformity

Release date 2012-08-02 13:51 Date of issue 2012-08-02 435821_eng.xml

Protection degree	EN 60529
General information	
Supplementary information	EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see www.pepperl-fuchs.com .