

Features

- Installation in Zone 0, Zone 1, Zone 2, Zone 21 and Zone 22

Dimensions (mm)**Technical data****Electrical specifications**

Operating voltage 100 ... 240 V AC, 50/60 Hz
12 ... 24 V AC/DC

Control gear Intrinsically Safe

Fitting type LED hand lamp

Lamps white high intensity LED

Number of lamps 8

Power 8 x 1 W

Cable length 15 m

Mechanical specifications

Cover fixing M8 stainless steel socket cap head screws

Protection degree IP66

Cable entry PG9 spiral cable gland

Material

Lamp cover Polycarbonate


Mass approx. 80 g (excluding cable)

Mounting 1 x moulded suspension hook

Ambient conditions

Ambient temperature -20 ... 40 °C (-4 ... 104 °F)

Data for application in connection with Ex-areas

EC-Type Examination Certificate BAS 00 ATEX 0315
Group, category, type of protection, temperature class  II 2 GD Ex ia IIC T4 , Ex iaD T180°C

International approvals

IECEx approval IECEx SIR 10.0077X

GOST-R approval GOST-R B00223

Conformity

| | |
|----------------------------|--|
| Protection degree | EN 60529 |
| General information | |
| Supplementary information | EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see www.pepperl-fuchs.com . |