



## **Features**

- · Cast Iron
- Installation in Zone 1, Zone 2, Zone 21 and Zone 22
- · Threaded cable entries
- · Padlockable switch

## **Dimensions (mm)**





Te	chn	ical	data

Electrical specifications	
Operating voltage	690 V
Operating current	100 A (AC21A)
Power	37 kW (AC23A) 30 kW (AC3)
Terminal capacity	50 mm <sup>2</sup>
Function	switch disconnetor
Number of poles	4
Auxiliary contacts	2 x n/o early break
Lockable	in 'OFF' position
Labeling	OFF - ON
Mechanical specifications	
Height	210 mm NOM.
Width	185 mm NOM.
Depth	200 mm NOM.
Enclosure cover	hinged non-detachable
Cover fixing	M6 stainless steel socket cap head screws
Fastener grade	A2-70
Protection degree	IP66
Cable entry	metric threaded
Number of cable entries	1 x M25 in face A 2 x M25 in face B all entries are fitted with Ex d sealing plugs
Material	
Enclosure	cast iron
Finish	painted black
Seal	one piece closed cell neoprene

approx. 20 kg

	Œ
	_
- 1	_
1	7
в	×
	•
	437890
- 1	0
	-
	. ~
-	S
	_
	9
	٠
٠	2013-01
1	
	·
	_1
1	m
	_
	•
i	$\vec{}$
- 1	·
	4
	d)
	=
	77
	SSIDE
	S
	=
•	$\overline{}$
	C
	- 5
	(I)
	æ
	Dat
	_
•	
:	2
:	2
	2
	2
	2
	2
	2
	1613:10
4. 4.	1613:10
4. 4.	2
	1613:10
4. 4.	1613:10
41 41 10	1613:10
41 41 10	1613:10
41 41 14	1613:10
41 41 14	1613:10
41 41 14	1613:10
41 41 14	1613:10
41 41 14	1613:10
41 41 10	1613:10
41 41 14	1613:10
41 41 41 4144	1613:10
41 41 14	1613:10
	1613:10
41 41 41 4144	1613:10
	1613:10
	1613:10
	1613:10
	1613:10
	1613:10
	1613:10
	1613:10
41 41 41 4144 11	ease date 2013-01-16 13:10
41 41 41 4144 11	ease date 2013-01-16 13:10
41 41 41 4144 11	ease date 2013-01-16 13:10
41 41 41 4144 11	ease date 2013-01-16 13:10
4. 4. 4. 4.44	ease date 2013-01-16 13:10

Mounting	2 x fabricated stainless steel mounting straps
Grounding	internal & external brass grounding terminals on base and lid
Ambient conditions	
Ambient temperature	-40 55 °C (-40 131 °F)
Data for application in connection with Exareas	
EC-Type Examination Certificate	SIRA 03 ATEX 1215
Group, category, type of protection, temperature class	<ul><li>⟨ओ   2 GD</li><li>Ex d   IB T5 Gb, Ex tb   IIC T95°C (ta +55°C)</li></ul>
International approvals	
IECEx approval	IECEx SIR 08.0055
GOST-R approval	GOST-R B01008
Conformity	
Protection degree	EN 60529
Switch	switch disconnector to IEC 60947-3
General information	
Supplementary information	EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see www.pepperlfuchs.com.