



Model Number


V15-G-YE5M-PVC-V15-G-ABG-Y908923

M12 connection cable, screened

Features

- Shield connected to pin 5 on both ends

Dimensions



Technical data

General specifications

Number of pins	5
Construction type	Socket, straight Connector, straight

Electrical specifications

Operating voltage	U_B	... 125 V
Operating current		max. 4 A
Volume resistance		< 5 mΩ


Ambient conditions

Ambient temperature	-25 ... 100 °C (-13 ... 212 °F) for temperatures over 80 °C (176 °F) reduced elongation at tear
---------------------	--

Mechanical specifications

Cable diameter	5.9 mm
Protection degree	IP67 / IP68 / IP69k
Material	
Contacts	CuSn / Au
Contact surface	Au
Handle	TPU , yellow
Cable	PVC
Slotted nut	Diecast zinc
Core isolation	PVC
Cable	
Color	yellow
Cores	4 x 0.34 mm ² , 1 x screen
Length	L 5 m
Flammability	flame resistant

Electrical connection



Release date: 2010-05-04 16:00 Date of issue: 2010-05-04 908923_ENG.xml

Subject to modifications without notice

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776-4411
fa-info@pepperl-fuchs.com

Copyright Pepperl+Fuchs
Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS
SENSING YOUR NEEDS