



### Model Number


**V3-WR-YE2M-PUR**

Cable socket, M8, 3-pin, PUR cable

### Features

- Snap locking

### Dimensions



### Technical data

#### General specifications

Number of pins	3
Connection 1	female connector
Construction type 1	right angle
Connection 2	cable end

#### Electrical specifications

Operating voltage	$U_B$	max. 125 V DC
Test voltage		> 1500 V <sub>eff</sub> AC
Operating current		max. 4 A
Volume resistance		< 5 mΩ

#### Ambient conditions

Ambient temperature	-25 ... 80 °C (-13 ... 176 °F)
Pollution Degree	3

#### Mechanical specifications

Pin diameter	1 mm	
Protection degree	IP67 / IP68 / IP69k	
Material		
Contacts	CuSn	
Contact surface	Ni/Au	
Body	TPU , yellow	
Cable	PUR	
Core insulation	PVC	
Cable	fine-strand, flexible	
Sheath diameter	Ø 4.4 mm	
Bending radius	10 x cable diameter	
Color	yellow	
Cores	3 x 0.25 mm <sup>2</sup>	
Length	L	2 m
Flammability		
Contact material	94 V-2	
Housing	94 V-2	
Wire	VW-1 flame rating from UL	
Note	M8 without thread	

#### Approvals and certificates

UL approval	cULus Listed, General Purpose
-------------	-------------------------------

### Electrical connection



1	-----	BN
3	-----	BU
4	-----	BK