

### Model Number


**V125-G-YE2M-PVC**

Female cordset, M12, 5-pin, PVC cable

### Features

- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Gold-plated and machined contacts
- Protection degree IP67 / IP68 / IP69K
- Suitable for 2-, 3- and 4-wire technology

### Dimensions



### Technical data

#### General specifications

Number of pins	5
Connection 1	socket
Construction type 1	straight
Threading 1	1/2"
Connection 2	cable end

#### Electrical specifications

Operating voltage	$U_B$	max. 125 V AC/DC
Test voltage		> 1500 V <sub>eff</sub> AC
Operating current		max. 4 A
Volume resistance		< 5 mΩ

#### Ambient conditions

Ambient temperature	-25 ... 105 °C (-13 ... 221 °F)
Pollution Degree	3

#### Mechanical specifications

Pin diameter	1 mm
Protection degree	IP68 / IP69K
Connection	1/2" UNF socket, straight


#### Material

Contacts	CuSn	
Contact surface	Ni/Au	
Body	TPU , yellow	
Cable	PVC	
Slotted nut	brass, nickel-plated	
Core insulation	PVC	
Cable	fine-strand, flexible	
Sheath diameter	Ø 5.9 mm	
Bending radius	10 x cable Diameter:	
Color	yellow	
Cores	5 x 0.34 mm <sup>2</sup>	
Length	L	2 m
Flammability		
Contact material	94 V-2	
Housing	94 V-2	
Cable	VW-1 flame rating from UL	

#### Approvals and certificates

UL approval	cULus Listed, General Purpose
-------------	-------------------------------

### Electrical connection



1	RD/WH
2	RD
3	GN
4	RD/YE
5	RD/BK