
XZCR1511062B1

jumper cable XZ - male straight M12 3-pin - female straight M12 3-pin - PUR 1m



Main	
Accessory / separate part category	Cabling accessory
Accessory / separate part type	Jumper cable

Complementary

Jumper cable end 1	M12 male, :3 pins (straight), fixing: screw-on	
Jumper cable end 2	M12 female, :3 pins (straight), fixing: screw-on	
Cable composition	3 x 0.5 mm ²	
Cable length	1 m	
Wire insulation material	PUR	
Cable outer diameter	5.2 mm	
[Ue] rated operational voltage	36 V DC 30 V AC	
[In] rated current	4 A	
Insulation resistance	>= 1000 MOhm	
Resistance across terminals	<= 5000 mOhm	
Product weight	0.065 kg	

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-590 °C (flexing) -3590 °C (static)
Ambient air temperature for storage	-35100 °C


Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0649 - Schneider Electric declaration of conformity

Product data sheet Dimensions Drawings

XZCR1511062B1

Dimensions



L: Lenght of cable

Product data sheet Connections and Schema

XZCR1511062B1

Connections and Schemes

