XZCRV2605V2X1

jumper cable XZ - male straight M8 4 pin - female straight M8 3 pin - PVC 1m



Main Accessory / separate Cabling accessory part category Accessory / separate Jumper cable part type

Complementary

Jumper cable end 2 M8 female, :3 pins (straight), fixing: screw-on Metal Cable composition 3 x 0.25 mm² Cable length 1 m Wire insulation material PVC Cable outer diameter 4.6 mm [Ue] rated operational voltage 300 V DC	
Cable composition 3 x 0.25 mm² Cable length 1 m Wire insulation material PVC Cable outer diameter 4.6 mm	
Cable length 1 m Wire insulation material PVC Cable outer diameter 4.6 mm	
Wire insulation material PVC Cable outer diameter 4.6 mm	
Cable outer diameter 4.6 mm	
Il let rated operational voltage 300 V DC	
250 V AC	
[In] rated current 3 A	
Insulation resistance >= 1000 MOhm	
Resistance across terminals <= 5000 mOhm	
Product weight 0.05 kg	


Environment

IP degree of protection	IP65 IP67
Ambient air temperature for operation	-2580 °C (static)
Ambient air temperature for storage	-2580 °C

Product data sheet Dimensions Drawings

XZCRV2605V2X1

Dimensions



Product data sheet Connections and Schema

XZCRV2605V2X1

Connections and Schemes

