



Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0823 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Эксплуатационные Характеристики
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	The warranty on the equipment is 18 months from the date of entry into service, as evidenced by a relevant document, but not more than 24 months from the date of delivery
-----------------	--

Main

Range	Prisma
Product name	Pack 160
IP degree of protection	IP30
Product or component type	Door
Enclosure mounting	Surface Flush with kit
Type of front cover	Transparent
Provided equipment	Keylock (key 405) Hinge (x2) Door Handle Other keylock and insert (to be ordered separately)

Complementary

Door opening side	Reversible
Number of locks	1
Opening size	130 °
Number of 18 mm modules per row	24
Total number of 18 mm modules	48
Enclosure/cubicle description	Pack enclosure - width 555 mm Extension enclosure - width 555 mm
Number of vertical modules (50 mm)	9
Number of horizontal rows	2
Enclosure material	Handle : polyamide Glass Cover frame : treated sheet steel
Quantity per set	Set of 1
Height	480 mm
Width	550 mm
Depth	32 mm
Product weight	3.3 kg

Surface finish	Matt Smooth
Colour	White RAL 9001

Environment

IK degree of protection	IK08 conforming to EN/IEC 62262
Standards	IEC 61439-2 IEC 61439-1
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder