

## ACF402

High-density equipment creates an environment where traditional air distribution methods are often not effective. Densely packed enclosures can cause IT equipment to overheat, resulting in downtime. The Rack Air Removal Unit SX captures exhaust heat, returns the warm air to the plenum and eliminates hot spots from the data center. Through automatic fan speed control based upon temperature, the fans will self-adjust for optimal performance. With a unit-mounted LCD display, users can view temperatures at the rack, monitor alarm conditions and adjust unit set points. The integrated network management card allows for remote monitoring and control. This space-saving solution mounts to the back of either the NetShelter SX or VX enclosure, requiring zero U space.





## Обзор

Описание	High-density equipment creates an environment where traditional air distribution methods are often not effective. Densely packed enclosures can cause IT equipment to overheat, resulting in downtime. The Rack Air Removal Unit SX captures exhaust heat, returns the warm air to the plenum and eliminates hot spots from the data center. Through automatic fan speed control based upon temperature, the fans will self-adjust for optimal performance. With a unit-mounted LCD display, users can view temperatures at the rack, monitor alarm conditions and adjust unit set points. The integrated network management card allows for remote monitoring and control. This space-saving solution mounts to the back of either the NetShelter SX or VX enclosure, requiring zero U space.
Название модели	Rack Air Removal Unit SX 100-240V 50/60HZ for NetShelter 750mm enclosures.
Включает	Documentation CD , Installation guide , Operations and maintenance manual
Стандартное время поставки	Usually in Stock
Распространение продуктов	Andorra , United Arab Emirates , Afghanistan , Antigua And Barbuda , Anguilla , Albania , Armenia , Netherlands Antilles , Angola , Argentina , Austria , Australia , Aruba , Azerbaijan , Bosnia And Herzegovina , Barbados , Bangladesh , Belgium , Burkina Faso , Bulgaria , Bahrain , Burundi , Benin , Bermuda , Brunei Darussalam , Bolivia , Brazil , Bahamas , Bhutan , Botswana , Belarus , Belize , Canada , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Central African Republic , Congo , Switzerland , Cote D'Ivoire , Cook Islands , Chile , Cameroon , China , Colombia , Costa Rica , Serbia And Montenegro , Cuba , Cyprus , Czech Republic , Germany , Djibouti , Denmark , Dominica , Dominican Republic , Algeria , Ecuador , Estonia , Egypt , Western Sahara , Spain , Ethiopia , Finland , Fiji , Falkland Islands (Malvinas) , France , Gabon , United Kingdom , Grenada , Georgia , French Guiana , Ghana , Gibraltar , Gambia , Guinea , Guadeloupe , Equatorial Guinea , Greece , Guatemala , Guyana , Hong Kong , Honduras , Croatia , Haiti , Hungary , Indonesia , Ireland , Israel , India , Iraq , Iran (Islamic Republic Of) , Iceland , Italy , Jamaica , Jordan , Japan , Kenya , SAINT KITTS AND NEVIS , KOREA, REPUBLIC OF , Kuwait , Cayman Islands , Kazakhstan , Lebanon , SAINT LUCIA , Liechtenstein , Sri Lanka , Liberia , Lesotho , Lithuania , Luxembourg , Latvia , Morocco , Moldova, Republic Of , Madagascar , Macedonia , Mali , Myanmar , Martinique , Mauritania , Malta , Mauritius , Malawi , Mexico , Malaysia , Mozambique , Namibia , Niger , Nigeria , Nicaragua , Netherlands , Norway , Nepal , New Zealand , Oman , Panama , Peru , Papua New Guinea , Philippines , Pakistan , Poland , Puerto Rico , Portugal , Paraguay , Reunion , Romania , Russian Federation , Rwanda , Saudi Arabia , Sudan , Sweden , Singapore , Slovenia , Slovakia (Slovak Republic) , Sierra Leone , Senegal , Somalia , El Salvador , Turks And Caicos Islands , Chad , Togo , Thailand , Turkmenistan , Tunisia , East Timor , Turkey , Trinidad And Tobago , Taiwan , TANZANIA, UNITED REPUBLIC OF , Ukraine , Uganda , United States , Uruguay , Uzbekistan , SAINT VINCENT AND THE GRENADINES , Venezuela , VIRGIN ISLANDS (UNITED STATES) , Viet Nam , Yemen , Mayotte , South Africa , Zambia , Zimbabwe

Купить

APC  ACF402

## Общие

Схемы отвода отработанного воздуха	Upflow , Ducted
Воздушный поток	755.12 lps

## Входной

Число сетевых шнуров	2
Номинальное входное напряжение	100 , 120 , 200 , 208 , 230
Входная мощность	1200 W
Входная частота	50/60 Hz
Тип входного соединения	IEC-320 C14 , NEMA 5-15P

## Коммуникационные средства и средства администрирования

Панель управления	Multi-function LCD status and control console
-------------------	---

## Физические

Максимальная высота	1918 mm
Максимальная ширина	737 mm
Максимальная глубина	254 mm
Масса нетто	77.27 kg
Масса брутто	100.91 kg
Цвет	Black

## Окружающей среды

Рабочий диапазон параметров окружающей среды	0 - 50 °C
Температура хранения	0 - 50 °C
Рабочий диапазон относительной влажности	0 - 95 %
Относительная влажность хранения	0 - 95 %
Высота над уровнем моря хранения	0-4500 meters
Уровень акустического шума на расстоянии 1 метра от поверхности устройства	79.000 dB

## Соответствие

Соответствие требованиям	CUL Listed , CE , EN 55022 Class A , EN 55024 , FCC Part 15 Class A , ICES-003 , IEC 61000-3-2 , IEC 61000-3-3 , UL Listed , VDE
Стандартная гарантия	1 year (parts only)