

TCSMCN1M1F10

Modbus shielded cable - M12 male connector -
M12 female connector - IP67 - 10 m



Main

| | |
|---------------------------------------|----------------------------------|
| Range of product | OsiSense XG |
| Accessory / separate part category | Connection accessories |
| Accessory / separate part type | Connecting cable |
| Accessory / separate part designation | Modbus shielded connecting cable |
| Accessory / separate part destination | Compact station Tap-off box |
| Cable length | 10 m |

Complementary

| | |
|-----------------------|--|
| Electrical connection | 1 male connector M12 straight (A coding) 1 female connector M12 straight (A coding) |
| Colour | Black |
| Product weight | 0.52 kg |

Environment

| | |
|-------------------------|------|
| IP degree of protection | IP67 |
|-------------------------|------|

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0615 - Schneider Electric declaration of conformity |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.