



### Main

|                            |                              |
|----------------------------|------------------------------|
| Range of product           | OsiSense XC                  |
| Series name                | Special format               |
| Product or component type  | Limit switch lever           |
| Device short name          | XCRZ                         |
| Product compatibility      | XCRT                         |
| Movement of operating head | Rotary                       |
| Type of operator           | Roller lever stainless steel |
| Type of approach           | Lateral approach             |
| Positive opening           | Without                      |

### Complementary

|                             |                    |
|-----------------------------|--------------------|
| Associated complete product | XCRT115<br>XCRT215 |
|-----------------------------|--------------------|

### Environment

|                                       |             |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -25...70 °C |
|---------------------------------------|-------------|

### Offer Sustainability

|                                  |                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                 |
| RoHS (date code: YYWW)           | Compliant - since 1010 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                     |
| Product environmental profile    | Available <a href="#">Download Product Environmental</a>                              |
| Product end of life instructions | Need no specific recycling operations                                                 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.