Characteristics

Product data sheet





Main

TTT COLUMN	
Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Rotary head
Product compatibility	XCKD XCKP XCKT XCMD
Associated lever	ZCY12 ZCY15 ZCY16 ZCY17 ZCY18 ZCY19 ZCY22 ZCY23 ZCY25 ZCY26 ZCY39 ZCY44 ZCY44 ZCY45 ZCY46 ZCY48 ZCY49 ZCY53 ZCY55 ZCY69 ZCY59 ZCY59 ZCY59 ZCY69 ZCY81 ZCY91

Associated body	ZCD21
	ZCD21M12 ZCD25
	ZCD26
	ZCD27
	ZCD28
	ZCD29
	ZCD29M12 ZCD31
	ZCD35
	ZCD37
	ZCD39
	ZCMD21C12
	ZCMD21L08R12 ZCMD21L08U78
	ZCMD21L1
	ZCMD21L2
	ZCMD21L5
	ZCMD21M12 ZCMD25L1
	ZCMD25L2
	ZCMD25L5
	ZCMD29C12
	ZCMD29L1 ZCMD29L2
	ZCMD29L2 ZCMD29L5
	ZCMD37L1
	ZCMD37L2
	ZCMD37L5
	ZCMD39L1 ZCMD39L2
	ZCMD39L5
	ZCMD41L1
	ZCMD41L2
	ZCMD41L5 ZCMD61C12
	ZCMD61C12 ZCMD61M12
	ZCMD69C12
	ZCMD81L1
	ZCMD81L2
	ZCMD81L5 ZCP21
	ZCP21M12
	ZCP25
	ZCP26
	ZCP27
	ZCP28 ZCP29
	ZCP29M12
	ZCP31
	ZCP35
	ZCP37 ZCP39
	ZCT21G11
	ZCT21N12
	ZCT21P16
	ZCT25G11
	ZCT25N12 ZCT25P16
	ZCT25P16 ZCT26G11
	ZCT26N12
	ZCT26P16
	ZCT27G11
	ZCT27N12 ZCT27P16
	ZCT28G11
	ZCT28N12
	ZCT28P16
Movement of operating head	Rotary
Type of operator	Without operating lever spring return metal
Type of approach	Lateral approach 2 directions

Complementary

Positive opening With



Environment

Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-4070 °C
Environmental characteristic	Standard environment

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0851 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

