

XZCC12FCP40B

female, M12, 4-pin, elbowed connector - cable gland Pg 7



Main

| | |
|------------------------------------|--|
| Accessory / separate part category | Cabling accessories |
| Accessory / separate part type | Connector |
| Electrical connection | Elbowed female connector M12, 4 pins |
| Collar material | Plastic |
| Status LED | Without |
| Cable connection | Screw terminal / wire size $\leq 0.75 \text{ mm}^2$ / clamping capacity 3...6 mm |

Complementary

| | |
|--------------------------------|---------------------------|
| Cable gland type | Pg 7 |
| Cable connector fixing | Screw-on |
| [Ue] rated operational voltage | 125 V AC 150 V DC |
| [In] rated current | 3 A |
| Enclosure material | Plastic |
| Insulating resistance | $> 1000 \text{ G}\Omega$ |
| Contact resistance | $\leq 8000 \mu\text{Ohm}$ |
| Product weight | 0.02 kg |

Environment


| | |
|---------------------------------------|-------------|
| IP degree of protection | IP67 |
| Ambient air temperature for operation | -40...85 °C |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0726 - Schneider Electric declaration of conformity |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Dimensions



(1) Cable gland : no. 7 plastic (Pg 7)

Connections and Schemes

