

ZCMD29C12

limit switch body ZCMD - 2NC - silver - snap
action - connection - M12



Main

| | |
|-------------------------------|--|
| Range of product | OsiSense XC |
| Series name | Standard format |
| Product or component type | Limit switch body |
| Device short name | ZCMD |
| Design | Miniature |
| Body type | Fixed |
| Associated head | ZCE01 ZCE02 ZCE06 ZCE07 ZCE08 ZCE09 ZCE10 ZCE11 ZCE13 ZCE14 ZCE21 ZCE24 ZCE27 ZCE28 ZCE29 ZCE62 ZCE63 ZCE64 ZCE65 ZCE66 ZCE67 ZCEF0 ZCEF2 ZCEG1 |
| Body material | Zamak |
| Number of poles | 2 |
| Contacts type and composition | 2 NC |
| Contacts operation | Snap action |

Complementary


| | |
|--|---|
| Product compatibility | XCMD |
| Electrical connection | Male connector M12, 5 pins |
| Contacts insulation form | Zb |
| Contacts material | Silver plated contacts |
| Positive opening | With |
| Minimum actuation speed | 0.01 m/min |
| [Ie] rated operational current | 0.22 A at 50 V, DC-13 conforming to EN/IEC 60947-5-1 appendix A 3 A at 50 V, AC-15 conforming to EN/IEC 60947-5-1 appendix A |
| [Ithe] conventional enclosed thermal current | 4 A |
| [Ui] rated insulation voltage | 60 V degree of pollution 3 conforming to IEC 60947-5-1 |
| Resistance across terminals | < 25 mOhm conforming to IEC 60255-7 category 3 |
| [Uimp] rated impulse withstand voltage | 0.8 kV conforming to IEC 60664 0.8 kV conforming to IEC 60947-1 |
| Short circuit protection | 4 A by gG cartridge fuse |

| | |
|-----------------------|--|
| Electrical durability | 5000000 cycles, DC-13 24 V, 3 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 2 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Width | 30 mm |
| Height | 50 mm |
| Depth | 16 mm |
| Product weight | 0.065 kg |

Environment

| | |
|-------------------------------------|-------------|
| Ambient air temperature for storage | -40...70 °C |
|-------------------------------------|-------------|

Offer Sustainability

| | |
|----------------------------------|--|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1001 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available  Download Product Environmental |
| Product end of life instructions | Need no specific recycling operations |