
XZCE03M125M

adaptor, metal - tapped hole M20 - for male connector, M12, 5-wire



Main Accessory / separate 5-wire connector adaptor part designation Accessory / separate Cabling accessories part category Accessory / separate Connector adaptor part type Cable composition 4 x 0.34 mm² + 1 x 0.5 mm² Thread type M20 x 1.5 [In] rated current 4 A

Complementary

Cable length	100 mm	
Total number of wires	5	
Electrical connection	1 male connector M12 5 straight	
Cable connector fixing	Screw-on	
Body material	Metal	
Insulation resistance	> 100000000 Ohm	
Resistance across terminals	<= 5000 mOhm	
[Ue] rated operational voltage	36 V DC 30 V AC	
Product weight	0.025 kg	

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-2580 °C

Offer Sustainability


Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 9830 - Schneider Electric declaration of conformity

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intellability of these products for specific user applications. It is the doung nation such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Product data sheet Dimensions Drawings

XZCE03M125M

Dimensions




(1) Thread size M20 x 1.5

Product data sheet Connections and Schema

XZCE03M125M

Connections and Schemes



BN: Brown BK: Black BU: Blue

Y/G : Yellow / Green WH : White