

# XUK2LAKSMM12T

photo-electric laser sensor -XUK -thru beam  
transmitter - Sn 30m -10..30VDC -M12



## Main

Range of product	OsiSense XU
Series name	Application assembly Application material handling
Electronic sensor type	Photo-electric sensor
Sensor name	XUK
Sensor design	Compact 50 x 50
Detection system	Thru beam
Material	Plastic
Type of output signal	Discrete
Supply circuit type	DC
Wiring technique	4-wire
Electrical connection	1 male connector M12, 4 pins
Product specific application	-
Emission	Red laser thru beam (class 1)
[Sn] nominal sensing distance	25 m thru beam need receiver XUK2LAPSMM12R

## Complementary

Enclosure material	ABS/PC
Lens material	PMMA
Maximum sensing distance	30 m thru beam
Add on output	Without
Add on input	Test
Status LED	1 LED (yellow) for output state 1 LED (green) for supply
[Us] rated supply voltage	10...28 V DC with reverse polarity protection
Supply voltage limits	10...30 V DC
Switching frequency	<= 500 Hz
Voltage drop	<= 2.4 V (closed state)
Current consumption	<= 30 mA (no-load)
Delay first up	< 300 ms
Delay response	< 1.2 ms
Delay recovery	< 1.2 ms
Setting-up	Using teach button or remote teaching
Depth	50 mm
Height	50 mm
Width	18 mm
Product weight	0.15 kg

## Environment

Product certifications	CE CULus Ecolab
Ambient air temperature for operation	-20...60 °C -20...50 °C, UL certified
Temperature for cleaning operation	-20...100 °C
Ambient air temperature for storage	-20...80 °C
Vibration resistance	7 gn, amplitude = +/- 1.5 mm (f = 10...55 Hz) conforming to IEC 60068-2-6

---

Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60947-5-2
IP degree of protection	IP67 conforming to IEC 60529 IP69K conforming to DIN 40050

---

### Offer Sustainability

---

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be Compliant

---