

Main

| Mairi | |
|----------------------------|---|
| Range of product | OsiSense XC |
| Series name | Special format |
| Product or component type | Limit switch head |
| Device short name | ZC2J |
| Head type | Rotary head |
| Product compatibility | XC2J |
| Associated lever | ZC2JY11 ZC2JY12 ZC2JY13 ZC2JY31 ZC2JY51 ZC2JY81 ZC2JY91 |
| Associated body | ZC2JC15 ZC2JC25 |
| Movement of operating head | Rotary |
| Type of operator | Without operating lever spring return |
| Type of approach | Lateral approach 1 direction programmable |
| | |

Complementary

| o implementary | | |
|------------------|---------------------------------|--|
| Switch actuation | From left or right CW or CCW | |
| Positive opening | Without | |
| Product weight | 0.21 kg | |
| Head material | Metal | |

Environment

| Ambient air temperature for operation | 10120 °C |
|---------------------------------------|------------------|
| Ambient air temperature for storage | 10120 °C |
| Environmental characteristic | High temperature |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended for and is not to be used for determining suitability or intendish products to specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.