

# XX630A3JCM12

ultrasonic sensor cylindrical M30 - Sn=8m - NO  
+NC NPN sync - M12



## Main

|                               |   |
|-------------------------------|---|
| Range of product              | OsiSense XX                                   |
| Sensor type                   | Ultrasonic sensor                             |
| Series name                   | General purpose                               |
| Sensor name                   | XX6   |
| Sensor design                 | Cylindrical M30                               |
| Detection system              | Diffuse                                       |
| [Sn] nominal sensing distance | 8 m adjustable with teach push-button         |
| Material                      | Plastic                                       |
| Type of output signal         | Discrete                                      |
| Discrete output function      | 1 NC + 1 NO                                   |
| Wiring technique              | 5-wire  |
| Discrete output type          | NPN   |
| [Us] rated supply voltage     | 12...24 V DC with reverse polarity protection |
| Electrical connection         | Male connector M12 5 pins                     |
| [Sd] sensing range            | 0.3...8 m                                     |
| Beam angle                    | 16 °  |
| IP degree of protection       | IP67 conforming to IEC 60529                  |

## Complementary

|   |  |
|---|--|
| Enclosure material                                | ULTEM  |
| Front material                                    | Epoxy  |
| Thread type                                       | M30 x 1.5  |
| Supply voltage limits                             | 10...28 V DC   |
| Function available                                | With synchronisation mode                              |
| [Sa] assured operating distance                   | 0.3...8 m (teach mode)                                 |
| Maximum differential travel                       | 12.7 mm  |
| Blind zone  | 0...300 mm   |
| Transmission frequency                            | 75 kHz   |
| Repeat accuracy                                   | 2.54 %   |
| Deviation angle from 90° of object to be detected | -5...5 °   |
| Minimum size of detected object                   | Cylinder diameter 50.8 mm 4.732 m                      |
| Status LED  | 1 LED (green/red (flashing)) for setting-up assistance |
| Current consumption                               | 50 mA  |
| Maximum switching current                         | 100 mA with overload and short-circuit protection      |
| Voltage drop                                      | < 1 V  |
| Switching frequency                               | <= 2 Hz  |
| Delay first up                                    | 800 ms   |
| Delay response                                    | 200 ms   |
| Delay recovery                                    | 200 ms   |
| Marking   | CE   |
| Threaded length                                   | 64.3 mm  |
| Height  | 44 mm  |
| Width   | 44 mm  |
| Depth   | 118 mm   |
| Product weight                                    | 0.11 kg  |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

|                                       |  |
|---------------------------------------|--|
| Standards                             | IEC 60947-5-2  |
| Ambient air temperature for operation | -20...60 °C  |
| Ambient air temperature for storage   | -40...80 °C  |
| Vibration resistance                  | +/-1 mm conforming to IEC 60068-2-6 10...55 Hz             |
| Shock resistance                      | 30 gn in all 3 axes for 11 ms conforming to IEC 60068-2-27 |
| Resistance to electrostatic discharge | 8 kV level 4 conforming to IEC 61000-4-2                   |
| Resistance to electromagnetic fields  | 10 V/m level 3 conforming to IEC 61000-4-3                 |
| Resistance to fast transients         | 1 kV level 3 conforming to IEC 61000-4-4                   |