XZCP29P12L10

pre-wired connectors XZ - straight female - M12 - 8 pins - cable PUR 10m



Main	
Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	Application

Complementary

o in promontary		
Electrical connection	Straight female connector, connector type: M12 8 pins	
Cable connector fixing	Screw-on	
Collar material	Stainless steel 316L	
Status LED	Without	
Cable length	10 m	
Cable outer diameter	6.1 mm	
Cable composition	8 x 0.25 mm ²	
Wire insulation material	PUR	
[Ue] rated operational voltage	30 V AC 36 V DC	
[In] rated current	2 A	
Contact resistance	<= 5000 μOhm	
Insulating resistance	>= 1 GΩ	
Product weight	0.47 kg	

Environment

LIMIOIIIICII		
IP degree of protection	IP67	
Ambient air temperature for storage	-4095 °C	

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be Compliant on 3Q2013

Product data sheet Connections and Schema

XZCP29P12L10

Connections and Schemes

Connectors



GY: Grey
PK: Pink
VT: Violet
BN: Brown
OG: Orange
WH: White
BU: Blue
BK: Black