Product data sheet Characteristics

XZCP0366L5

pre-wired connectors XZ - elbowed female - Ø 8 mm - 3 pins - cable PUR 5m





Main	
Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	General purpose

Complementary

Electrical connection	Elbowed female connector, connector type: Ø 8 mm 3 pins	
Cable connector fixing	Clip-on	
Status LED	2 PNP LEDs	
Cable length	5 m	
Cable outer diameter	5.2 mm	
Cable composition	3 x 0.34 mm ²	
Wire insulation material	PUR	
[Ue] rated operational voltage	1030 V DC	
[In] rated current	4 A	
Contact resistance	<= 5000 μOhm	
Insulating resistance	>= 1 GΩ	
Product weight	0.11 kg	

Environment

IP degree of protection	IP65 IP67	
Ambient air temperature for operation	-4080 °C (static) -580 °C (flexing)	
Ambient air temperature for storage	-4080 °C	

Offer Sustainability

Oner Oustainability	
Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0649 - 🖾 Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available 🗟 Download Product Environmental
Product end of life instructions	Available 🗟 Download End Of Life Manual



Product data sheet Dimensions Drawings

XZCP0366L5

Dimensions



L: Lenght of cable



XZCP0366L5

Connections and Schemes

Connector



BU : Blue

BN : Brown BK : Black

BK : Black

Connections and Schemes

LED Connection



BN : Brown

BK : Black

BU : Blue

GN : Green YW : Yellow

(1) Signal

