

XUB0SPSWL2

photo-electric sensor - XUB - multi - 90° - Sn
0..7m - 12..24VDC - cable 2m



Main

| | |
|-------------------------------|---|
| Range of product | OsiSense XU |
| Series name | Application food and beverage multimode |
| Electronic sensor type | Photo-electric sensor |
| Sensor name | XUB |
| Sensor design | Cylindrical M18 |
| Detection system | Multimode |
| Material | Stainless steel |
| Line of sight type | 90° lateral |
| Type of output signal | Discrete |
| Supply circuit type | DC |
| Wiring technique | 3-wire |
| Discrete output type | PNP |
| Discrete output function | 1 NO or 1 NC programmable |
| Electrical connection | Cable |
| Cable length | 2 m |
| Product specific application | - |
| Emission | Infrared diffuse Infrared diffuse with background suppression Infrared thru beam Red polarised reflex |
| [Sn] nominal sensing distance | 1.5 m polarised reflex need reflector XUZC50 7 m thru beam need a transmitter XUB0SKSWL2T 0.11 m diffuse with background suppression 0.2 m diffuse |

Complementary

| | |
|---------------------------|---|
| Enclosure material | Stainless steel : 304 CU |
| Lens material | PMMA |
| Maximum sensing distance | 2 m polarised reflex 0.11 m diffuse with background suppression 0.3 m diffuse 10 m thru beam |
| Output type | Solid state |
| Wire insulation material | PvR |
| Status LED | 1 LED (green) for output state 1 LED (red) for supply on 1 LED (yellow) for stability |
| [Us] rated supply voltage | 12...24 V DC with reverse polarity protection |
| Supply voltage limits | 10...36 V DC |
| Switching capacity in mA | <= 100 mA (overload and short-circuit protection) |
| Switching frequency | <= 250 Hz |
| Voltage drop | 1.5 V (closed state) |
| Current consumption | 35 mA (no-load) |
| Delay first up | < 200 ms |
| Delay response | < 2 ms |
| Delay recovery | < 2 ms |
| Setting-up | Self-training |
| Diameter | 18 mm |

| | |
|----------------|---------|
| Length | 78 mm |
| Product weight | 0.11 kg |

Environment

| | |
|---------------------------------------|---|
| Product certifications | CE CSA UL |
| Ambient air temperature for operation | -25...55 °C |
| Ambient air temperature for storage | -40...70 °C |
| Vibration resistance | 7 gn, amplitude = +/- 1.5 mm (f = 10...55 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 30 gn (duration = 11 ms) conforming to IEC 60068-2-27 |
| IP degree of protection | IP65 double insulation conforming to IEC 60529 IP67 double insulation conforming to IEC 60529 IP69K double insulation conforming to DIN 40050 |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0821 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |