Product data sheet Characteristics

XZCPA1865L10

pre-wired connectors XZ - straight female - 1/2"20 UNF - 3 pins - cable PVC 10m



Main	
Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	Application

Complementary

Electrical connection	Straight female connector, connector type: 1/2"20 UNF 3 pins
Cable connector fixing	Screw-on
Collar material	Stainless steel 316L
Status LED	Without
Cable length	10 m
Cable outer diameter	5 mm
Cable composition	3 x 0.34 mm²
Wire insulation material	PVC
[Ue] rated operational voltage	250 V AC 300 V DC
[In] rated current	4 A
Contact resistance	<= 5000 μOhm
Insulating resistance	>= 1 GΩ
Product weight	0.4 kg

Environment

IP degree of protection	IP69K
Ambient air temperature for operation	-2585 °C (static)
Ambient air temperature for storage	-35100 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0601 - 🖾 Schneider Electric declaration of conformity



Product data sheet Dimensions Drawings

XZCPA1865L10

Dimensions



L: Lenght of cable



Product data sheet Connections and Schema

XZCPA1865L10

Connections and Schemes

Connectors



GN : Green RD/ Red / White WH : RD/ Red / Black BK :

