XGSZ12E4501

OsiSense XG cable M12 D coded to RJ45 - Ethernet - 1m



Main

Range of product	OsiSense XG
Accessory / separate part category	Connection accessories
Accessory / separate part type	Connecting cable
Product or component type	Ethernet copper cable
Product compatibility	XGSZ33ETH XUW XGSZ33EIP
Accessory / separate part destination	Ethernet network

Complementary

Cable length	1 m
Transmission rate	100 Mbit/s
Transmission support medium	2 twisted shielded pairs
Communication network category	5e
AWG gauge	AWG 26
Electrical connection	1 male connector, M12 straight connector with 4 pin(s) - encoding type: D coding 1 male connector, RJ45 straight connector with 4 pin(s)
Conductor material	Copper
Cover material	PUR
Product weight	0.075 kg

Environment

IP degree of protection	IP67	
Standards	EIA/TIA-568 IEC 60754-1 ISO/IEC 11801 Ed.2, 2002	
Environmental characteristic	RoHS compliant	

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1210 - Schneider Electric declaration of conformity

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability of these products for specific user applications. This the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Product data sheet Connections and Schema

XGSZ12E4501

Wiring Diagram

