



Photoelectric sensors
W27-3, Photoelectric proximity sensor,
Background suppression

WTB27-302641S08



Model Name > [WTB27-302641S08](#)
Part No. > [1029141](#)



Illustration may differ

At a glance

- Precise background suppression with no scanning distance drift
- PinPoint technology: intense red LED with consistent light spot
- Resistant to ambient light, optical reflections, and crosstalk from other photoelectric devices
- Sensing range adjustment with potentiometer or teach-in
- Operating temperature: -40 °C to +60 °C
- Flexible sensing ranges and hysteresis settings
- Key lock function, remote teach, quality monitoring
- Diagnostics messages (contamination and short-circuit)

Your benefits

- PinPoint technology can replace laser photoelectric proximity sensors in some applications. No laser safety regulations and a longer operating life due to PinPoint technology
- Less downtime due to ASIC (application-specific integrated circuit) chip technology by SICK
- Resistant to ambient light, optical reflections, and immune to crosstalk from other photoelectric devices, reducing false detection
- Durable housing with reinforced mounting holes withstands harsh conditions
- Reliable operation in harsh environments with temperatures as low as -40 °C
- Quick and easy format adjustment
- Easy monitoring of sensor status
- Key lock function and parameter download prevent incorrect settings
- Simple sensor cloning



Features

Sensor/detection principle:	Photoelectric proximity sensor, Background suppression
Dimensions (W x H x D):	24.6 mm x 80.6 mm x 54 mm
Housing design (light emission):	Rectangular
Sensing range max.:	100 m ... 250 mm, 30 mm ... 1,100 mm ^{1) 2)}
Sensing range:	100 mm ... 250 mm
Type of light:	Visible red light
Light source:	LED ³⁾
Wave length:	660 nm
Special features:	With semiconductor relay 24 VDCWith semiconductor relay 24 VDC, Sensing range potentiometer fixed with glueSensing range potentiometer fixed with glue, Sensing range preset at 250 mm on an object with 18 % remission

Adjustment: Potentiometer fixed with glue

Light spot size (distance): Ø 15 mm (500 mm)


¹⁾ Object with 90 % reflectance (referred to standard white DIN 5033) ²⁾ Object with 18 % reflectance (referred to grey) ³⁾ Average service life of 100,000 h at T_A = +25 °C

Mechanics/electronics


Supply voltage: 10 V DC ... 30 V DC ¹⁾
Ripple: ≤ 5 V_{pp} ²⁾
Power consumption: ≤ 50 mA ³⁾
Output type: Semiconductor relay
Switching current (switching voltage): 100 mA (20 V AC), 100 mA (30 V DC)
Response time: ≤ 3 ms
Switching frequency: 200 Hz ⁴⁾
Connection type: Connector Q6, 6-pin, AC/UC-coding
Circuit protection::: A, C, E ^{5) 6) 7)}
Protection class: II ⁸⁾
Weight: 120 g
Special device: ✓
Housing material: ABS, Plastic
Optics material: PMMA
Enclosure rating: IP 65
Ambient operating temperature: -40 °C ... 60 °C
Ambient storage temperature: -40 °C ... 75 °C
UL File No.: NRKH.E181493 & NRKH7.E181493

¹⁾ Limit values, operation in short-circuit protected network max. 8 A ²⁾ May not exceed or fall short of V_S tolerances ³⁾ Without load ⁴⁾ With light/dark ratio 1:1 ⁵⁾ A =
V_S connections reverse-polarity protected ⁶⁾ C = interference suppression ⁷⁾ E = semiconductor relay short-circuit protected ⁸⁾ Reference voltage 50 V DC


Dimensional drawing




Adjustments possible



Connection diagram



Connection type



Australia

Phone +61 3 9457 0600
1800 33 48 02 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail marketing@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Česká republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail info@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6881000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 5309 2112
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederland

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail sick@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail sales.gsg@sick.com

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886 2 2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 88 65 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 (800) 325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com