



Absolute encoders ATM60 SSI

ATM60-A1L12X12



Model Name > ATM60-A1L12X12
Part No. > 1030007



Illustration may differ

At a glance

- Extremely rugged, tried-and-tested absolute multiturn encoder with a resolution of up to 26 bits
- Mechanical interface: face mount flange, servo flange, blind hollow shaft and extensive adapter accessories
- Zero-set and preset functions via hardware or software
- No battery required
- Electrical interface: SSI with gray or binary code type
- Electronically adjustable, configurable resolution
- Rotary axis function (optional) also for non-binary resolutions (per revolution) and decimal numbers (number of revolutions)
- Magnetic scanning

Your benefits

- Fewer variants are required since one freely programmable encoder offers all singleturn and multiturn resolutions
- Easy setup due to various connectivity options (cable, M23)
- Less maintenance and a long service life reduce overall costs
- Application flexibility due to easily interchangeable collets for the blind hollow shaft
- Quick commissioning using the zero set/preset function either at the press of the button on the device or via software
- Increased productivity due to highly reliable shock and vibration resistance
- Worldwide availability and service ensure quick and reliable customer service



Performance

| | |
|--------------------------------------|------------------------|
| Max. number of steps per revolution: | 4,096 |
| Max. number of revolutions: | 4,096 |
| Resolution power: | 4,096 x 4,096 |
| Resolution: | 12 bit x 12 bit |
| Error limits: | ± 0.25 ° |
| Repeatability (Ta not constant): | 0.1 ° |
| Measuring step: | 0.043 ° |
| Initialization time: | 1,050 ms ¹⁾ |

¹⁾ Valid positional data can be read once this time has elapsed

Mechanical data

| | |
|--------------------------------------|-----------------------------------|
| Mechanical interface: | Solid shaft, Servo flange |
| Shaft diameter: | 6 mm |
| Mass: | 0.5 kg |
| Permissible Load capacity of shaft: | 300 N (radial), 50 N (axial) |
| Moment of inertia of the rotor: | 35 gcm ² |
| Bearing lifetime: | 3.6 x 10 ⁹ revolutions |
| Max. angular acceleration: | 500,000 rad/s ² |
| Shaft material: | Stainless steel |
| Flange material: | Aluminum |
| Housing material: | Die-cast aluminum |
| Start up torque with shaft seal: | 2.5 Ncm |
| Start up torque without shaft seal: | 0.5 Ncm |
| Operating torque with shaft seal: | 1.8 Ncm |
| Operating torque without shaft seal: | 0.3 Ncm ¹⁾ |
| Shaft length: | 10 mm |

¹⁾ If the shaft seal has been removed by the customer

Electrical data

| | |
|--|--------------------------------------|
| Operating voltage range: | 10 V ... 32 V |
| MTTFd: mean time to dangerous failure: | 150 a (EN ISO 13849-1) ¹⁾ |
| Connection type: | Cable, 12-pin, radial, 3 m |
| Code type: | Binary, Gray |
| Code sequence: | CW/CCW |
| Power consumption max. without load: | 0.8 W |

¹⁾ This product is a standard product and does not constitute a safety component as defined in the Machinery Directive.

Calculation based on nominal load of components, average ambient

temperature 40°C, frequency of use 8760 h/a. All

electronic failures are considered hazardous. For more information, see document no. 8015532.

Interfaces

| | |
|--|---|
| Electrical interface: | SSI |
| Interface signals: | Clock +, Clock -, Data +, Data-, Programming interface: RS-422 ¹⁾ |
| Clock frequency: | 1 MHz ²⁾ |
| SET (electronic adjustment): | H-active (L ≡ 0 - 4,7 V, H ≡ 10 - Us V) |
| CW/CCW (counting sequence when turning): | L-active (L ≡ 0 - 1,5 V, H ≡ 2,0 - Us V) |
| Parameterising data: | Number of revolutions, Code type, Electronic adjustment, Number of steps per revolution |

¹⁾ For higher clock frequencies, choose synchronous SSI ²⁾


Ambient data

| | |
|------|--|
| EMC: | (according to EN 61000-6-2 and EN 61000-6-3) |
|------|--|

| | |
|--------------------------------|---|
| Enclosure rating:: | IP 43 (according to IEC 60529), without shaft seal, on encoder flange not sealed, IP 65 (according to IEC 60529), without shaft seal, on encoder flange sealed, IP 67 (according to IEC 60529), with shaft seal |
| Permissible relative humidity: | 98 % |
| Working temperature range: | -20 °C ... +85 °C |
| Storage temperature range: | -40 °C ... +100 °C, without package |
| Resistance to shocks: | 100 g, 6 ms (according to EN 60068-2-27) |
| Resistance to vibration: | 20 g, 10 Hz ... 2,000 Hz (according to EN 60068-2-6) |

1) 2) 3)
With mating connector fitted

Dimensional drawing



Australia

Phone +61 3 9457 0600
1800 33 48 02 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail marketing@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Česká republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail info@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6881000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 5309 2112
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederland

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail sick@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail sales.gsg@sick.com

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886 2 2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 88 65 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 (800) 325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com