



Absolute encoders ARS60 SSI/Parallel

ARS60-H4K08192



Model Name > [ARS60-H4K08192](#)
Part No. > [1035846](#)



At a glance

- Absolute singleturn encoder
- Resolution: up to 15 bits (32,768 increments)
- Electrical interface: SSI with gray code type or gray capped
- Electrical interface: Parallel with gray, gray capped, binary, BCD code type
- Zero-set function
- Mechanical interfaces: face mount flange, servo flange, blind and through hollow shaft
- Enclosure rating: Up to IP66

Your benefits

- Freely programmable resolution (up to 15 bits)
- Simple zero adjustment directly by press of a button on the encoder or via signal line (cable version)
- Suitable for all mounting methods thanks to individual mechanical interfaces
- A basic device for flexible use thanks to simple interchangeable collets for blind hollow shaft and through hollow shaft
- Versions with cable and M23 connector outlet available in axial and radial designs



Performance

Max. number of steps per revolution:	8,192
Max. number of revolutions:	1
Resolution power:	8,192 x 1
Error limits:	0.035 ° (binary number of steps) 0.046 ° (non-binary number of steps)
Repeatability (Ta not constant):	0.005 °
Measuring step deviation:	0.005 °, 0.016 °
Measuring step:	360 ° /number of lines
Initialization time:	80 ms ¹⁾

¹⁾ Valid positional data can be read once this time has elapsed

Mechanical data

Mechanical interface:	Solid shaft, Face mount flange
Shaft diameter:	10 mm
Start up torque:	0.4 Ncm
Operating torque:	0.3 Ncm

Permissible Load capacity of shaft:	20 N (radial) 10 N (axial)
Maximum operating speed:	10,000 /min (without shaft seal) 6,000 /min (with shaft seal) ¹⁾
Moment of inertia of the rotor:	54 gcm ²
Bearing lifetime:	3.6 x 10 ⁹ revolutions
Max. angular acceleration:	500,000 rad/s ²
Operation of zero-set:	≥ 100 ms ²⁾

¹⁾ If the shaft seal has been removed by the customer ²⁾ Only with shaft stationary (note initialisation time)

Electrical data

Operating voltage range:	10 V DC ... 32 V DC
Operating power consumption (no load):	90 mA

Interfaces

Electrical interface:	Cable, 22-pin, radial, 1.5 m
-----------------------	------------------------------

Ambient data

EMC:	According to EN 61000-6-2 and EN 61000-6-3 ¹⁾
Enclosure rating:	IP 66, according to IEC 60529
Permissible relative humidity:	90 % (condensation of the optical scanning not permitted)
Working temperature range:	-20 °C ... 85 °C
Storage temperature range:	-40 °C ... 100 °C
Resistance to shocks:	50 g (according to EN 60068-2-27)
Resistance to vibration:	20 g, 10 Hz ... 2,000 Hz (according to EN 60068-2-6)

¹⁾

Technical drawing of a mechanical part, showing three views: front view, side view, and detail view.

Front View:

- Top hole: M4 8 tief
- Top hole diameter: $\varnothing 48 \pm 0.1$
- Top hole depth: 120°
- Top hole position: $+ \varnothing 0.2 B$
- Top hole diameter: $\varnothing 60$
- Top hole depth: 28°
- Top hole diameter: $\varnothing 60$
- Top hole depth: 24
- Top hole diameter: $\varnothing 60$

Side View:

- Top hole diameter: $\varnothing 59.5$
- Top hole depth: $\varnothing 36.18$
- Top hole diameter: $\varnothing 10.17$
- Top hole depth: 9
- Top hole diameter: $\varnothing 10.17$
- Top hole depth: 18
- Top hole diameter: $\varnothing 10.17$
- Top hole depth: 19 ± 1
- Top hole diameter: $\varnothing 10.17$
- Top hole depth: 13.5

Detail View:

- Top hole diameter: $\varnothing 10.17$
- Top hole depth: 20
- Top hole diameter: $\varnothing 10.17$
- Top hole depth: 10
- Top hole diameter: $\varnothing 10.17$
- Top hole depth: 10
- Top hole diameter: $\varnothing 10.17$
- Top hole depth: 10
- Top hole diameter: $\varnothing 10.17$
- Top hole depth: 10

The top diagram shows a timing diagram for a 13-bit code disc. A 'Clock +' signal is shown as a series of pulses. Above the clock, a double-headed arrow labeled 'Data format singleturn' spans the duration of 13 clock cycles. Below the clock, the cycles are numbered 1 through 13. To the right of the clock, a horizontal line is labeled 'singleturn'.

The bottom diagram is a table representing the data format for 1 revolution of the code disc. The table has 4 rows and 15 columns. The first 13 columns are labeled A-1 through A-13. The next two columns are labeled 'tm-T/2' and '2ⁿ'. The final column is labeled 'A'. The data is as follows:

A-1	A-2	A-3	A-4	A-5	A-6	A-7	A-8	A-9	A-10	A-11	A-12	A-13	tm-T/2	2 ⁿ	A
x	x	x	x	x	x	x	x	x	x	x	x	x	0	1	8192 13
x	x	x	x	x	x	x	x	x	x	x	x	0	0	1	4096 12
x	x	x	x	x	x	x	x	x	x	x	0	0	0	1	2048 11
x	x	x	x	x	x	x	x	x	x	0	0	0	0	1	1024 10

Below the table, a double-headed arrow labeled 'Code disc for 1 revolution' spans the width of the first 13 columns. To the right of the table, an upward-pointing arrow is labeled 'resolution per revolution'.

Australia

Phone +61 3 9457 0600
1800 33 48 02 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail marketing@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Česká republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail info@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6881000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 5309 2112
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederland

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail sick@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail sales.gsg@sick.com

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886 2 2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 88 65 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 (800) 325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com