



## Photoelectric sensors MH15, Photoelectric proximity sensor, energetic

MHT15-P4317S05



**Model Name** > **MHT15-P4317S05**  
**Part No.** > **1041225**



*Illustration may differ*

#### At a glance

- Energetic variant with a long sensing distance
- Sensitivity control via 270° potentiometer
- Indicator LED with an active switching output and operating reserve
- Straight or right-angle housing designs available
- 100 mm or 350 mm sensing distances for straight housing; 90 mm or 250 mm (each with 90% remission) for right-angle housings
- Mounting accessories (M18 nuts and snap ring) are included
- IP 69K-tested housing offers a long service life that withstands harsh environments

#### Your benefits

- Reliably detects and positions parts without a reflector, saving installation time and costs
- Shortest M18 body on the market, saving installation space
- Flush mounting via snap ring reduces setup time and prevents obstructions to material flow on conveyor systems
- MHT15 is compatible with competitor sensors for easy replacement that saves installation time and costs
- IP 69K-tested housing offers a long service life that withstands harsh environments, reducing maintenance time and costs



#### Features


|                                  |                                           |
|----------------------------------|-------------------------------------------|
| Sensor/detection principle:      | Photoelectric proximity sensor, energetic |
| Housing design (light emission): | Cylindrical, straight                     |
| Housing length:                  | 36.8 mm                                   |
| Thread diameter (housing):       | M18 x 1                                   |
| Optical axis:                    | axial                                     |
| Sensing range max.:              | 10 mm ... 100 mm <sup>1)</sup>            |
| Sensing range:                   | 10 mm ... 90 mm                           |
| Type of light:                   | Infrared light                            |
| Light source:                    | LED <sup>2)</sup>                         |
| Wave length:                     | 950 nm                                    |
| Angle of dispersion:             | Ca. 4.5 °                                 |
| Special features:                | Health output                             |
| Adjustment:                      | Potentiometer, 270 °                      |
| Light spot size (distance):      | Ø 20 mm (100 mm)                          |

1) Object with 90 % reflectance (referred to standard white, DIN 5033) 2) Average service life of 100,000 h at  $T_A = +25\text{ °C}$


## Mechanics/electronics

|                                |                                                   |
|--------------------------------|---------------------------------------------------|
| Supply voltage:                | 10 V DC... 30 <sup>1)</sup>                       |
| Ripple:                        | $\leq 5\text{ V}_{pp}$ <sup>2)</sup>              |
| Power consumption:             | 30 <sup>3)</sup>                                  |
| Output type:                   | PNP                                               |
| Switching mode:                | Light switching                                   |
| Output current $I_{max.}$ :    | $\leq 100\text{ mA}$                              |
| Response time:                 | $\leq 1.25\text{ ms}$ <sup>4)</sup>               |
| Switching frequency:           | 400 Hz <sup>5)</sup>                              |
| Connection type:               | Connector M12, 4-pin                              |
| Circuit protection:::          | A, C, D <sup>6)</sup> <sup>7)</sup> <sup>8)</sup> |
| Protection class:              | III                                               |
| Weight:                        | 7 g                                               |
| Special device:                | ✓                                                 |
| Housing material:              | ABS, Plastic                                      |
| Optics material:               | PMMA                                              |
| Enclosure rating:              | IP 67<br>IP 69K                                   |
| Ambient operating temperature: | -25 ... +55 °C                                    |
| Ambient storage temperature:   | -25 ... +70 °C                                    |
| UL File No.:                   | NRKH.E189383 & NRKH7.E189383                      |
| Signal voltage PNP HIGH/LOW:   | $U_v - (< 2,9\text{ V})/\text{ca. } 0\text{ V}$   |

1) Limit values 2) May not exceed or fall short of  $V_S$  tolerances 3) Without load 4) Signal transit time with resistive load 5) With light/dark ratio 1:1 6)  $A = V_S$   
connections reverse-polarity protected 7) C = interference suppression 8) D = outputs overcurrent and short-circuit protected




### Adjustments possible



- [1] Sensitivity sclae 270°
- [2] Yellow LED indicator:- lights  
continuously:light reception> reserve factor 1  
.3- blinks: light reception < reserve factor 1.3 but > swit

## Connection diagram



## Connection type



**Australia**

Phone +61 3 9457 0600  
1800 33 48 02 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail marketing@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Česká republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail info@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6881000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 5309 2112  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederland**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail sick@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail sales.gsg@sick.com

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886 2 2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 88 65 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 (800) 325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)