



## Safety light curtains miniTwin4

C4MT-07824ABB04FE0



**Model Name** > [C4MT-07824ABB04FE0](#)  
**Part No.** > [1207292](#)



#### At a glance

- Type 4 (IEC 61496), SIL3 (IEC 61508), PL e (EN ISO 13849)
- Compact cross section (15 mm x 32 mm) with no dead zones
- Cascadable twin stick design - sender and receiver in a single housing
- Customized protective field heights in 60-mm increments from 120 mm to 1,200 mm
- Typical scanning ranges 0 m ... 5 m
- Intelligent, software-free configuration of external device monitoring (EDM) and reset function (RES)
- M12, 5-pin device connection

#### Your benefits

- Cost-effective machine integration: its small design, cascadable features and incremental protective field heights enable a flexible adjustment to the machine design
- Standardization saves time and resources because of more straightforward logistics, order entry and service
- Simplified handling and setup: Software-free, almost fully automatic commissioning and intuitive operation with sustainable optics
- Bright LED display provides fast alignment, easy start up and clear protective field visualization ensure quick diagnostics
- End-to-end coverage in cascadable applications eliminates dead zones and shortens the safety distance, increasing productivity
- Application-specific brackets provide increased flexibility and reduce installation time



#### Safety-related parameters

Type:	Type 4 (IEC 61496)
Safety integrity level:	SIL3 (IEC 61508) SILCL3 (EN 62061)
Category:	category 4 (EN ISO 13849)
Performance level:	PL e (EN ISO 13849)
PFHd:	Cascaded systems: $1.3 \cdot 10^{-8}$ (EN ISO 13849)
TM (mission time):	20 a (EN ISO 13849)
Safe state in the event of a fault:	At least one OSSD is in the OFF state.

#### Functions

Restart interlock:	✓
Restart interlock (delivery status):	Deactivated
External device monitoring (EDM):	✓
External device monitoring (delivery status):	Deactivated
Beam coding:	✓
Automatic beam coding:	✓
Cascaded:	✓
Safe SICK device communication via EFI/SDL:	-

## Features

---

Resolution:	24 mm
Protective field height:	780 mm
Scanning range:	0 m ... 4 m
Typical range:	0 m ... 5 m
Response time:	≤ 13 ms <sup>1)</sup>
Synchronization:	Optical, without separate synchronization

<sup>1)</sup> Standalone devices, no cascaded systems. Other response times see operating instructions.

## Mechanical data

---

Housing cross-section (incl. system connection):	15 mm x 32 mm
Housing material:	Aluminum alloy ALMGSI 0.5
Weight:	280 g

## Electrical data

---

Protection class:	III (EN 61140)
Supply voltage:	24 V DC (19.2 V DC ... 28.8 V DC)
Residual ripple:	≤ 10 % <sup>1)</sup>
Power consumption:	≤ 3 A <sup>2)</sup>
Type of output:	PNP semiconductors, short-circuit protected, cross-circuit monitored <sup>3)</sup>
Switching voltage HIGH:	24 V DC (VS - 2.25 V DC ... VS)
Switching voltage LOW:	2 V DC
Switching current:	300 mA

<sup>1)</sup> Within the limits of  $V_S$  <sup>2)</sup> Maximum power consumption of a host/guest/guest system with 1,200 mm protective field height and a resolution of 14 mm <sup>3)</sup> Applies to the voltage range between -30 V and +30 V

## Interfaces

---


Electrical connection:	Connector M12, 5-pin
Connection type extension connection:	Female connector M12, 5-pin
Cable length:	700 mm
Conductor cross-section:	0.34 mm <sup>2</sup>
Permitted cable length:	≤ 20 m <sup>1)</sup>
Configuration method:	Hard wired
Display elements:	LEDs
Integration via Flexi Soft safety controller:	CANopenDeviceNetEtherCATEtherNet/IPModbus TCPPROFIBUS DPPROFINET <sup>2)</sup>

<sup>1)</sup> <sup>2)</sup> For further information on Flexi Soft, please see sens:Control - safe control solutions product catalog or -> [www.sick.com/FlexiSoft](http://www.sick.com/FlexiSoft)

## Ambient data

Enclosure rating:	IP 65 (EN 60529)
Ambient operating temperature:	-20 °C ... +55 °C
Storage temperature:	-25 °C ... +70 °C
Air humidity:	15 % ... 95 %, non-condensing
Vibration resistance:	5 g, 10 Hz ... 55 Hz (EN 60068-2-6)
Shock resistance:	10 g, 16 ms (EN 60068-2-27)

## Dimensional drawing



**Australia**

Phone +61 3 9457 0600  
1800 33 48 02 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail marketing@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Česká republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail info@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6881000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 5309 2112  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederland**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail sick@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail sales.gsg@sick.com

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886 2 2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 88 65 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 (800) 325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)