



## Photoelectric sensors V18, Photoelectric proximity sensor, energetic

VTE18-4P4740



**Model Name** > [VTE18-4P4740](#)  
**Part No.** > [6013335](#)



*Illustration may differ*

#### At a glance

- Cylindrical M18 housing
- Three sensing distances of 200 mm, 400 mm or 800 mm
- 3- or 4-wire
- Straight or right-angle housing
- Metal or plastic housing

#### Your benefits

- Simple, standardized design ensures easy mounting, alignment and replacement
- Compact, space-saving design easily fits in tight application spaces



#### Features

|                                  |                                           |
|----------------------------------|-------------------------------------------|
| Sensor/detection principle:      | Photoelectric proximity sensor, energetic |
| Housing design (light emission): | Cylindrical, straight, straight           |
| Housing length:                  | 78 mm                                     |
| Thread diameter (housing):       | M18 x 1                                   |
| Optical axis:                    | axial                                     |
| Sensing range max.:              | 5 mm ... 400 mm <sup>1)</sup>             |
| Sensing range:                   | 5 mm ... 350 mm                           |
| Type of light:                   | Infrared light                            |
| Light source:                    | LED <sup>2)</sup>                         |
| Light spot (distance):           | 20 mm (400 mm)                            |
| Sensitivity adjustment:          | Potentiometer, 270°                       |
| Angle of dispersion:             | 2.8 °                                     |

<sup>1)</sup> Object with 90 % reflectance (referred to standard white DIN 5033) <sup>2)</sup> Average service life of 100,000 h at T<sub>A</sub> = +25 °C

#### Mechanics/electronics


|                                   |                                                                            |
|-----------------------------------|----------------------------------------------------------------------------|
| Supply voltage:                   | 10 V DC ... 30 V DC <sup>1)</sup>                                          |
| Residual ripple:                  | ≤ 10 % <sup>2)</sup>                                                       |
| Power consumption:                | ≤ 30 mA <sup>3)</sup>                                                      |
| Output type:                      | PNP, Light/dark-switching, Selectable via L/D control wire, open collector |
| Output current I <sub>max</sub> : | 100 mA                                                                     |
| Response time:                    | ≤ 2 ms <sup>5)</sup>                                                       |
| Switching frequency:              | 250 Hz <sup>6)</sup>                                                       |
| Electrical connection:            | Connector M12, 4-pin                                                       |

|                                |                                    |
|--------------------------------|------------------------------------|
| Circuit protection:::          | A, B, C, D <sup>7) 8) 9) 10)</sup> |
| Protection class:              | III                                |
| Weight:                        | 100 g                              |
| Housing material:              | PBT/PC                             |
| Optics material:               | PMMA                               |
| Enclosure rating:              | IP 67                              |
| Ambient temperature operation: | -25 °C ... 70 °C                   |
| UL File-No.:                   | UL No. NMFT2.E175606               |


Control wire open: dark-switching D.ON;

1) Limit values 2) May not exceed or fall short of  $V_S$  tolerances 3) Without load 4) Control wire open: dark-switching D.ON 5) Signal transit time with resistive load 6) With light/dark ratio 1:1 7)  $A = V_S$  connections reverse-polarity protected 8) B = inputs and output reverse-polarity protected 9) C = interference suppression 10) D = outputs overcurrent and short-circuit protected


## Dimensional drawing




Adjustments possible



Connection diagram




Characteristic curve



Connection type



Sensing range diagram



**Australia**

Phone +61 3 9457 0600  
1800 33 48 02 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail marketing@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Česká republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail info@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6881000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 5309 2112  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederland**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail sick@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail sales.gsg@sick.com

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886 2 2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 88 65 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 (800) 325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)