



## Photoelectric sensors W100, Photoelectric proximity sensor, Background blanking

WT100-N4410



**Model Name** > **WT100-N4410**  
**Part No.** > **6028616**



*Illustration may differ*

#### At a glance

- Standard miniature housing with M3 threaded mounting holes
- Optics with standard red LED or bright light LED
- Available as a background blanking sensor or as an energetic proximity sensor
- Light/dark switching and sensitivity adjustment via rotary switch possible (depending on type)
- Wide variety of accessories available (depending on type)

#### Your benefits

- Highly visible light spot allows for quick and easy alignment
- M3 threaded mounting holes provide easy installation

**Product will be phased out and can be ordered until 31.12.2015.**



#### Features

|                                  |                                                     |
|----------------------------------|-----------------------------------------------------|
| Sensor/detection principle:      | Photoelectric proximity sensor, Background blanking |
| Dimensions (W x H x D):          | 11 mm x 31 mm x 20 mm                               |
| Housing design (light emission): | Rectangular                                         |
| Sensing range max.:              | 4 mm ... 140 mm <sup>1)</sup>                       |
| Sensing range:                   | 10 mm ... 100 mm                                    |
| Type of light:                   | Visible red light                                   |
| Light source:                    | LED <sup>2)</sup>                                   |
| Wave length:                     | 680 nm                                              |
| Focus adjustable:                | -                                                   |
| Adjustment:                      | Potentiometer, 270 °                                |
| Light spot size (distance):      | Ø 8 mm (90 mm)                                      |

<sup>1)</sup> Object with 90 % reflectance (referred to standard white, DIN 5033) <sup>2)</sup> Average service life of 100,000 h at T<sub>A</sub> = +25 °C


#### Mechanics/electronics

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| Supply voltage:                   | 10 V DC ... 30 V DC <sup>1)</sup> |
| Residual ripple:                  | ± 10 % <sup>2)</sup>              |
| Power consumption:                | ≤ 30 mA <sup>3)</sup>             |
| Output type:                      | NPN, open collector               |
| Switching mode:                   | Light/dark switching              |
| Switching mode selector:          | Manually selectable               |
| Output current I <sub>max</sub> : | ≤ 100 mA                          |
| Response time:                    | ≤ 0.5 ms <sup>4)</sup>            |


|                                |                                                   |
|--------------------------------|---------------------------------------------------|
| Switching frequency:           | 1,000 Hz <sup>5)</sup>                            |
| Electrical connection:         | Connector M8, 4-pin                               |
| Circuit protection:::          | A, B, D <sup>6)</sup> <sup>7)</sup> <sup>8)</sup> |
| Weight:                        | 9 g                                               |
| Polarisation filter:           | -                                                 |
| Special device:                | -                                                 |
| Optics material:               | PMMA                                              |
| Enclosure rating:              | IP 65                                             |
| Ambient temperature operation: | -25 °C ... +55 °C                                 |
| Ambient storage temperature:   | -40 °C ... +70 °C                                 |
| UL File No.:                   | NRKH2.E300503 & NRKH8.E300503                     |
| Signal voltage NPN HIGH/LOW:   | Approx. $V_S / < 1.8 \text{ V}$                   |
| Housing material:              | ABS/PC/POM, Plastic                               |

<sup>1)</sup> Limit values, operation in short-circuit protected network max. 8 A    <sup>2)</sup> May not exceed or fall short of  $V_S$  tolerances    <sup>3)</sup> Without load    <sup>4)</sup> Signal transit time with resistive load  
<sup>5)</sup> With light/dark ratio 1:1    <sup>6)</sup> A =  $V_S$  connections reverse-polarity protected    <sup>7)</sup> B = inputs and output reverse-polarity protected    <sup>8)</sup> D = outputs overcurrent and short-circuit protected

### Dimensional drawing




## Adjustments possible




- |1| LED indicator orange: switching output active
- |2| LED indicator green: power on
- |3| Sensing range adjustment: potentiometer
- |4| Light/ dark rotary switch: L = light switching, D = dark switching

## Connection diagram




Characteristic curve



- |1| Sensing range on black, 6 % remission
- |2| Sensing range on gray, 18 % remission
- |3| Sensing range on white, 90 % remission

Sensing range diagram




- |1| Sensing range on black, 6 % remission
- |2| Sensing range on gray, 18 % remission
- |3| Sensing range on white, 90 % remission

■ Sensing range      ■ Sensing range typ. max.

- ① Sensing range on black, 6 % remission
- ② Sensing range on gray, 18 % remission
- ③ Sensing range on white, 90 % remission

## Connection type

---



**Australia**

Phone +61 3 9457 0600  
1800 33 48 02 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail marketing@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Česká republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail info@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6881000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 5309 2112  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederland**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail sick@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail sales.gsg@sick.com

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886 2 2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 88 65 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 (800) 325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)