



## Photoelectric sensors V180-2, Photoelectric proximity sensor, energetic

VTE180-2P41187



**Model Name** > [VTE180-2P41187](#)  
**Part No.** > [6037487](#)



*Illustration may differ*

#### At a glance

- Lowest-cost M18 housing sensor on the market
- Long sensing distances: 100 mm, 400 mm, 800 mm (max. 1,100 mm)
- Bright power and signal LEDs with 360° visibility
- Wide product portfolio solves a broad range of applications
- High switching frequencies up to 1000 Hz
- Available in a metal housing for applications in harsh environments
- Optical axis selectively axial or radial (90°)

#### Your benefits

- Lowest-cost M18 cylindrical sensor on the market reduces installation costs
- Bright red sender LED simplifies alignment and saves installation time
- Bright power and signal LEDs with 360° visibility offer quick and simple troubleshooting, reducing installation and maintenance costs
- The flat and smooth lens reduces the collection of dust and dirt, ensuring safe operation with less maintenance and fewer costs



#### Features

|                                  |                                           |
|----------------------------------|-------------------------------------------|
| Sensor/detection principle:      | Photoelectric proximity sensor, energetic |
| Housing design (light emission): | Cylindrical, straight                     |
| Housing length:                  | 62.5 mm                                   |
| Thread diameter (housing):       | M18 x 1                                   |
| Optical axis:                    | axial                                     |
| Sensing range max.:              | 1 mm ... 1,100 mm <sup>1)</sup>           |
| Sensing range:                   | 1 mm ... 800 mm <sup>2)</sup>             |
| Type of light:                   | Visible red light                         |
| Light source:                    | LED <sup>3)</sup>                         |
| Wave length:                     | 645 nm                                    |
| Angle of dispersion:             | Ca. 1.2 °                                 |
| Adjustment:                      | Potentiometer, 270 °                      |
| Light spot size (distance):      | Ø 30 mm (800 mm)                          |

<sup>1) 2)</sup> Object with 90 % reflectance (referred to standard white, DIN 5033) <sup>3)</sup> Average service life of 100,000 h at T<sub>A</sub> = +25 °C


#### Mechanics/electronics

|                  |                                   |
|------------------|-----------------------------------|
| Supply voltage:  | 10 V DC ... 30 V DC <sup>1)</sup> |
| Residual ripple: | ± 10 % <sup>2)</sup>              |

|                                    |                                                     |
|------------------------------------|-----------------------------------------------------|
| Power consumption:                 | $\leq 30 \text{ mA}$ <sup>3)</sup>                  |
| Output type:                       | PNP, open collector <sup>4)</sup>                   |
| Switching mode:                    | Light/dark switching <sup>5)</sup>                  |
| Switching mode selector:           | Selectable via L/D control wire                     |
| Output current I <sub>max.</sub> : | $\leq 100 \text{ mA}$                               |
| Response time:                     | $\leq 0.5 \text{ ms}$ <sup>6)</sup>                 |
| Switching frequency:               | 1,000 Hz <sup>7)</sup>                              |
| Electrical connection:             | Cable, 4-wire, 2 m <sup>8)</sup>                    |
| Cable material:                    | PVC                                                 |
| Conductor cross-section:           | 0.18 mm <sup>2</sup>                                |
| Cable diameter:                    | Ø 3.8 mm                                            |
| Circuit protection:::              | A, B, D <sup>9)</sup> <sup>10)</sup> <sup>11)</sup> |
| Protection class:                  | III                                                 |
| Weight:                            | 62 g                                                |
| Housing material:                  | Plastic, PBT/PC                                     |
| Optics material:                   | PMMA                                                |
| Enclosure rating:                  | IP 67                                               |
| Items supplied:                    | Fastening nuts (2 x)                                |
| Ambient temperature operation:     | -25 °C ... +55 °C                                   |
| Ambient storage temperature:       | -40 °C ... +70 °C                                   |
| Signal voltage PNP HIGH/LOW:       | Approx. V <sub>S</sub> - 1.8 V / 0 V                |


<sup>1)</sup> Limit values, operation in short-circuit protected network max. 8 A    <sup>2)</sup> May not exceed or fall short of V<sub>S</sub> tolerances    <sup>3)</sup> Without load    <sup>4) 5)</sup> Control wire open: dark-switching D.ON    <sup>6)</sup> Signal transit time with resistive load    <sup>7)</sup> With light/dark ratio 1:1    <sup>8)</sup> Do not bend below 0 °C    <sup>9)</sup> A = V<sub>S</sub> connections reverse-polarity protected    <sup>10)</sup> B = inputs and output reverse-polarity protected    <sup>11)</sup> D = outputs overcurrent and short-circuit protected

## Dimensional drawing




- [1] Connector M12, 4-pin
- [2] Connection cable 2 m
- [3] Sensitivity control (potentiometer, 270°)
- [4] LED indicator orange: switching output active
- [5] LED indicator green: strength indicator
- [6] fastening nuts (2 x); width across 22, PC

## Adjustments possible




- [3] Sensitivity adjustment 270°
- [4] LED indicator orange: switching output active
- [5] LED indicator green

Connection diagram




Characteristic curve




- |1| Sensing range on white, 90 % remission
- |2| Sensing range on grey, 18 % remission
- |3| Sensing range on black, 6 % remission


Connection type



Sensing range diagram



Light spot size



**Australia**

Phone +61 3 9457 0600  
1800 33 48 02 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail marketing@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Česká republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail info@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6881000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 5309 2112  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederland**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail sick@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail sales.gsg@sick.com

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886 2 2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 88 65 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 (800) 325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)