



## Level sensors Vibrating level switch, LFB330

LFB330-XXGBVXPT0750



**Model Name** > LFB330-XXGBVXPT0750  
**Part No.** > 6042780



*Product may differ  
from illustration*

#### At a glance

- Several housing materials and electrical outputs available
- Commissioning without filling
- Process temperature up to 250 °C
- Tube extension up to 6 m
- Immune to deposit formation
- Very high repeatability
- Aseptic versions according to EHEDG and FDA available, CIP and SIP resistant
- ATEX and marine certifications available

#### Your benefits

- Easy installation and commissioning, no calibration necessary
- Easy operation and integration, saves time
- Maintenance-free sensor, reduces downtime
- Testing in place possible - no mounting required, which reduces installation time
- Flexible and robust system for a multitude of applications
- Tube extension allows for safe vertical mounting
- Universal technology works in all kinds of liquids



#### Features

|                        |                   |
|------------------------|-------------------|
| Medium:                | Fluids            |
| Measurement:           | Switch            |
| Probe length:          | 750 mm            |
| Process pressure:      | -1 bar ... 64 bar |
| Process temperature:   | -50 °C ... 150 °C |
| WHG approval:          | -                 |
| Fill material density: | 0.5 ... 2.5       |

#### Performance

|                             |                          |
|-----------------------------|--------------------------|
| Accuracy of sensor element: | ± 2 mm                   |
| Repeatability:              | 1                        |
| Viscosity:                  | 0.1 mPas ... 10,000 mPas |
| Response time:              | 500 ms                   |

#### Mechanical data

|                     |                    |
|---------------------|--------------------|
| Housing material:   | Plastic            |
| Process connection: | G 3/4 A PN 64/316L |

|                  |                                             |
|------------------|---------------------------------------------|
| Wetted parts:    | Stainless steel 316L (optional Ra ≤ 0.8 µm) |
| Sensor material: | Stainless steel 1.4404                      |


#### Electrical data

|                        |                                                 |
|------------------------|-------------------------------------------------|
| Temperature drift:     | 0,03 mm/K                                       |
| Enclosure rating:      | IP 66                                           |
| Residual ripple:       | ≤ 5 Vpp                                         |
| Power consumption:     | < 10 mA                                         |
| Protection class:      | 0, 1                                            |
| Initialization time:   | 2 s                                             |
| Output signal:         | Transistor output PNP/ NPN: 10 V DC ... 55 V DC |
| Hysteresis:            | 2 mm                                            |
| Output current:        | < 300 mA                                        |
| Signal voltage HIGH:   | Uv - 3 V                                        |
| Signal voltage LOW:    | < 1 V                                           |
| Capacitive load:       | 100 Ω                                           |
| Inductive load:        | ≤ 1 H                                           |
| Electrical connection: | M20 x 1.5                                       |


#### Ambient data

|                                |                  |
|--------------------------------|------------------|
| Ambient temperature operation: | -40 °C ... 70 °C |
| Ambient storage temperature:   | -40 °C ... 80 °C |


#### Dimensional drawing




## Instruction for installation



## Ambient temperature - process temperature




Influence of the process temperature on the switching point




Influence of the process temperature to the switching point




Influence of the product density on the switching point



PNP action



NPN action



**Australia**

Phone +61 3 9457 0600  
1800 33 48 02 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail marketing@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Česká republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail info@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6881000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 5309 2112  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederland**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail sick@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail sales.gsg@sick.com

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886 2 2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 88 65 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 (800) 325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)